



# **ROCK FILTER UNITS**

Natural Protection for the environment



## SUBSEA PROTECTION SYSTEMS







#### **CABLE**

- PROTECTION
- STABILIZATION
- SPAN SUPPORT

### **MONOPILE**

SCOUR PROTECTION

#### **ROCK BAGS**

Durability under UV exposure up to 50 years submerged, the rock filter bag offers a quick solution thanks to its high flexibility, enabling it to contour into the most un-even surfaces.

They are an environmentally friendly solution, being manufactured from 61% of recycled materials.

Туре	Mesh Size	Rocks Particle Diameter	Unit Weight, Rock Bag empty	Dimensions in meters, Rock Bag installed			Applicable Velocity	
				Diameter	Height	Vol	Unit	Grouped
2te RockBag	25mm	50 ~ 200mm	6kg	1.9m	0.4m	1.24m <sup>3</sup>	3.1m/sec	4.7m/sec
4te RockBag	25mm	50 ~ 200mm	13kg	2.4m	0.6m	2.5m <sup>3</sup>	3.5m/sec	5.3m/sec
8te Rock Bag	50mm	75 ~ 200mm	48kg	3.0m	0.7m	5.0m <sup>3</sup>	3.9m/sec	5.9m/sec

Specific Gravity of rocks 2.5-2.55

## Roman Stone Construction Company

Telephone: 631 202 0640 Email: <u>info@romanstoneco.com</u> Website: <u>www.romanstoneco.com</u> Subsea Protection Systems Ltd

Telephone: +44 (0)1493 600 700 Email: <u>enquiries@sps-gb.com</u> Website: <u>www.sps-gb.com</u>